


## Stahl-Preßfassungen

für PTFE-Glattschlauch T1 und PTFE-Wellenschlauch W1

### Carbon steel ferrules

for PTFE-hose T1 and PTFE-convoluted hose W1



SWISS-HYDRAULIK

Schlauch Hose		Maßzahlen Dimensions			Preßmaße crimp-dimensions			Bestell-Nummer Order-No.
DN	inch	D1	D2	L	T1	T2	W1	
05	1/8"	9,5	13,0	24	10,8	*)	*)	PF - W1 - DN 05
06	1/4"	11,0	15,0	28	12,0	*)	12,0	PF - W1 - DN 06
08	5/16"	15,5	19,1	32	14,1	*)	14,1	PF - W1 - DN 08/10
10	3/8"	15,5	19,1	32	16,0	*)	16,0	PF - W1 - DN 08/10
12	1/2"	20,0	25,0	34	20,9	*)	20,9	PF - W1 - DN 12
16	5/8"	25,0	30,0	36	24,5	*)	24,5	PF - W1 - DN 16
20	3/4"	28,0	33,0	39	28,0	*)	28,0	PF - W1 - DN 20
25	1"	37,0	42,0	47	34,0	*)	34,0	PF - W1 - DN 25
32	1 1/4"	43,0	47,5	54	-	-	40,0	PF - W1 - DN 32
40	1 1/2"	49,8	55,0	65	-	-	47,1	PF - W1 - DN 40
50	2"	63,0	68,5	75	-	-	60,1	PF - W1 - DN 50

## Edelstahl-Preßfassungen

für PTFE-Glattschlauch T1 und PTFE-Wellenschlauch W1

### Stainless steel ferrules

for PTFE-hose T1 and PTFE-convoluted hose W1

Schlauch Hose		Maßzahlen Dimensions			Preßmaße crimp-dimensions			Bestell-Nummer Order-No.
DN	inch	D1	D2	L	T1	T2	W1	
05	1/8"	9,5	13,0	24	10,8	*)	*)	P6 - DN 05
06	1/4"	11,0	15,0	28	12,0	*)	12,0	P6 - DN 06
08	5/16"	15,5	19,1	32	14,1	*)	14,1	P6 - DN 08/10
10	3/8"	15,5	19,1	32	16,0	*)	16,0	P6 - DN 08/10
12	1/2"	20,0	25,0	34	20,9	*)	20,9	P6 - DN 12
16	5/8"	25,0	30,0	36	24,5	*)	24,5	P6 - DN 16
20	3/4"	28,0	33,0	39	28,0	*)	28,0	P6 - DN 20
25	1"	37,0	42,0	47	34,0	*)	34,0	P6 - DN 25
32	1 1/4"	43,0	47,5	54	-	-	40,0	P6 - DN 32
40	1 1/2"	49,8	55,0	65	-	-	47,1	P6 - DN 40
50	2"	63,0	68,5	75	-	-	60,1	P6 - DN 50